


ALC® Wafer Check Valves



The ALC® is an in-line, spring assisted, single guided "wafer" check valve designed to prevent "water hammer" and "reverse" flow. The lightweight compact design fits between mating flanges and meets API 594 Face-to-Face dimensions. The ALC® is an easy to maintain check valve for applications involving liquids, gases or steam. Tapped holes are provided in the body for lifting lugs to assist with installation. (10" & larger only)

All temperature ratings are for standard valves.

Results 1 - 25 of 36

Prod. #	Class	Size	Dimension A	B (Dia.)	Cv	Cracking Pressure CP	Body
522H1B4A5	150/300	DN 50 2 in	2.38 in 60 mm	4 in 108 mm	120	0.5 psig 0.034 bar	A216 WCB
525H1B4A5	150/300	DN 50 2 in	2.38 in 60 mm	4 in 108 mm	120	0.5 psig 0.034 bar	A351 CF8M
522J1B4A5	150/300	DN 65 2.5 in	2.62 in 67 mm	5 in 127 mm	205	0.5 psig 0.034 bar	A216 WCB
525J1B4A5	150/300	DN 65 2.5 in	2.62 in 67 mm	5 in 127 mm	205	0.5 psig 0.034 bar	A351 CF8M
522K1B4A5	150/300	DN 80 3 in	2.88 in 73 mm	6 in 146 mm	260	0.5 psig 0.034 bar	A216 WCB
525K1B4A5	150/300	DN 80 3 in	2.88 in 73 mm	6 in 146 mm	260	0.5 psig 0.034 bar	A351 CF8M
522L1B4A5	150/300	DN 100 4 in	2.88 in 73 mm	7 in 178 mm	430	0.5 psig 0.034 bar	A216 WCB
525L1B4A5	150/300	DN 100 4 in	2.88 in 73 mm	7 in 178 mm	430	0.5 psig 0.034 bar	A351 CF8M
522N1B4A5	150/300	DN 150 6 in	3.88 in 99 mm	10 in 248 mm	825	0.5 psig 0.034 bar	A216 WCB
525N1B4A5	150/300	DN 150 6 in	3.88 in 99 mm	10 in 248 mm	825	0.5 psig 0.034 bar	A351 CF8M
522O1B4A5	150/300	DN 200 8 in	5 in 127 mm	12 in 305 mm	1310	0.5 psig 0.034 bar	A216 WCB
525O1B4A5	150/300	DN 200 8 in	5 in 127 mm	12 in 305 mm	1310	0.5 psig 0.034 bar	A351 CF8M
522P1B4A5	150/300	DN 250 10 in	5.75 in 146 mm	14 in 359 mm	1875	0.5 psig 0.034 bar	A216 WCB
525P1B4A5	150/300	DN 250 10 in	5.75 in 146 mm	14 in 359 mm	1875	0.5 psig 0.034 bar	A351 CF8M
522R1B4A5	150/300	DN 300 12 in	7.12 in 181 mm	16 in 419 mm	2525	0.5 psig 0.034 bar	A216 WCB
525R1B4A5	150/300	DN 300 12 in	7.125 in 181 mm	16 in 419 mm	2525	0.5 psig 0.034 bar	A351 CF8M
522S1A4A5	150	DN 350 14 in	7.25 in 184 mm	17 in 448 mm	2950	0.5 psig 0.034 bar	A216 WCB
522S1B4A5	300	DN 350 14 in	8.75 in 222 mm	19 in 483 mm	3275	0.5 psig 0.034 bar	A216 WCB
525S1A4A5	150	DN 350 14 in	7.25 in 184 mm	17 in 448 mm	2950	0.5 psig 0.034 bar	A351 CF8M
525S1B4A5	300	DN 350 14 in	8.75 in 222 mm	19 in 483 mm	3275	0.5 psig 0.034 bar	A351 CF8M
522T1A4A5	150	DN 400 16 in	7.5 in 191 mm	20 in 511 mm	3330	0.5 psig 0.034 bar	A216 WCB
522T1B4A5	300	DN 400 16 in	9.13 in 232 mm	21 in 537 mm	4100	0.5 psig 0.034 bar	A216 WCB
525T1A4A5	150	DN 400 16 in	7.5 in 191 mm	20 in 516 mm	3330	0.5 psig 0.034 bar	A351 CF8M
525T1B4A5	300	DN 400 16 in	9.125 in 232 mm	20 in 516 mm	4100	0.5 psig 0.034 bar	A351 CF8M
522U1A4A5	150	DN 450 18 in	8 in 203 mm	22 in 546 mm	3475	0.5 psig 0.034 bar	A216 WCB

Results 1 - 25 of 36