


DLC® Flanged Check Valves



The DFT® Model DLC® is a corrosion resistant, dependable, versatile and economical spring assisted, in-line check valve for a wide range of applications. Whether the fluid is liquid, gas or steam, the DLC® provides tight shut-off and protects other equipment in the system from water hammer. Its stainless steel construction insures a long service life. Inconel® X-750 spring is standard

Results 1 - 12 of 12

Prod. #	Class	Size	Dimension A	Dimension B	Cv	Cracking Pressure CP
9400	150	DN 15 0.5 in	4.25 in 108 mm	3.50 in 89 mm	7	0.29 psig 0.020 bar
9401	150	DN 20 0.75 in	4.62 in 117 mm	3.88 in 99 mm	13	0.24 psig 0.017 bar
9402	150	DN 25 1 in	5.00 in 127 mm	4.25 in 108 mm	22	0.36 psig 0.025 bar
9404	150	DN 40 1.5 in	6.50 in 165 mm	5.00 in 127 mm	54	0.24 psig 0.017 bar
9405	150	DN 50 2 in	8.00 in 203 mm	6.00 in 152 mm	93	0.42 psig 0.029 bar
9407	150	DN 80 3 in	9.50 in 241 mm	7.50 in 191 mm	180	0.20 psig 0.014 bar
9410	300	DN 15 0.5 in	6.00 in 152 mm	3.75 in 95 mm	7	0.29 psig 0.020 bar
9411	300	DN 20 0.75 in	7.00 in 178 mm	4.62 in 117 mm	13	0.24 psig 0.017 bar
9412	300	DN 25 1 in	8.50 in 216 mm	4.88 in 124 mm	22	0.36 psig 0.025 bar
9414	300	DN 40 1.5 in	9.50 in 241 mm	6.12 in 155 mm	54	0.24 psig 0.017 bar
9415	300	DN 50 2 in	10.50 in 267 mm	6.50 in 165 mm	93	0.23 psig 0.016 bar
9417	300	DN 80 3 in	12.50 in 318 mm	8.25 in 210 mm	180	0.20 psig 0.014 bar

Results 1 - 12 of 12