


GLC® Flanged Check Valves



The DFT® Model GLC® Silent Check Valve is a spring-assisted, center guided, in-line, flanged check valve that provides reliable, low maintenance service for a wide range of fluids and pressure/temperature combinations. The valve consists of a body, seat, spring, disc with stem and guide bushing. Some valves have body or gasket seals. The DFT® GLC® check valve has the advantage of minimum pressure loss with silent, non-slam operation.

Results 1 - 25 of 114

Prod. #	Class	Size	Dimension A	Dimension B	Cv	Cracking Pressure CP	Body
9503	150 RF	DN 25 1 in	4.50 in 114 mm	4.25 in 108 mm	17	0.85 psig 0.059 bar	A216 Grade WCB
9551	150 RF	DN 40 1.5 in	5.75 in 146 mm	5.00 in 127 mm	35	0.29 psig 0.020 bar	A216 Grade WCB
9575-2	150 RF	DN 50 2 in	6.25 in 159 mm	6.00 in 152 mm	63	0.29 psig 0.020 bar	A216 Grade WCB
9599-1	150 RF	DN 65 2.5 in	7.00 in 178 mm	7 in 178 mm	100	0.18 psig 0.012 bar	A216 Grade WCB
9623-2	150 RF	DN 80 3 in	7.50 in 191 mm	7.50 in 191 mm	148	0.20 psig 0.014 bar	A216 Grade WCB
9647-1	150 RF	DN 100 4 in	8.50 in 216 mm	9 in 229 mm	260	0.49 psig 0.034 bar	A216 Grade WCB
9671	150 RF	DN 125 5 in	9.50 in 241 mm	10 in 254 mm	415	0.28 psig 0.019 bar	A216 Grade WCB
9695-2	150 RF	DN 150 6 in	10 in 254 mm	11 in 279 mm	620	0.41 psig 0.028 bar	A216 Grade WCB
9719-1	150 RF	DN 200 8 in	12 in 305 mm	13.50 in 343 mm	1030	0.41 psig 0.028 bar	A216 Grade WCB
9743-1	150 RF	DN 250 10 in	14 in 356 mm	16 in 406 mm	1630	0.55 psig 0.038 bar	A216 Grade WCB
9767-1	150 RF	DN 300 12 in	18 in 457 mm	19 in 483 mm	2370	0.47 psig 0.032 bar	A216 Grade WCB
9787-1	150 RF	DN 350 14 in	21 in 533 mm	21 in 533 mm	3500	0.52 psig 0.036 bar	A216 Grade WCB
9807-1	150 RF	DN 400 16 in	22.50 in 572 mm	23.50 in 597 mm	5100	0.51 psig 0.035 bar	A216 Grade WCB
9827-1	150 RF	DN 450 18 in	24 in 610 mm	25 in 635 mm	6400	0.59 psig 0.041 bar	A216 Grade WCB
9843-1	150 RF	DN 500 20 in	24 in 610 mm	27.50 in 699 mm	7700	0.49 psig 0.034 bar	A216 Grade WCB
9859	150 RF	DN 600 24 in	28 in 711 mm	32 in 813 mm	11100	0.44 psig 0.030 bar	A216 Grade WCB
9509	300 RF	DN 25 1 in	4.75 in 121 mm	4.88 in 124 mm	19	0.85 psig 0.059 bar	A216 Grade WCB
9557	300 RF	DN 40 1.5 in	6.00 in 152 mm	6.13 in 156 mm	35	0.29 psig 0.020 bar	A216 Grade WCB
9581-3	300 RF	DN 50 2 in	6.25 in 159 mm	6.50 in 165 mm	63	0.29 psig 0.020 bar	A216 Grade WCB
9605-1	300 RF	DN 65 2.5 in	7.25 in 184 mm	7.50 in 191 mm	100	0.18 psig 0.012 bar	A216 Grade WCB
9629-2	300 RF	DN 80 3 in	7.88 in 200 mm	8.25 in 210 mm	148	0.20 psig 0.014 bar	A216 Grade WCB
9653-1	300 RF	DN 100 4 in	9.13 in 232 mm	10 in 254 mm	267	0.48 psig 0.033 bar	A216 Grade WCB
9677	300 RF	DN 125 5 in	10.38 in 264 mm	11 in 279 mm	415	0.28 psig 0.019 bar	A216 Grade WCB
9701-1	300 RF	DN 150 6 in	11 in 279 mm	12.50 in 318 mm	620	0.39 psig 0.027 bar	A216 Grade WCB
9725-1	300 RF	DN 200 8 in	13 in 330 mm	15 in 381 mm	933	0.45 psig 0.031 bar	A216 Grade WCB

Results 1 - 25 of 114