


SCV® Threaded In-Line Check Valves



The DFT® Model SCV® is a corrosion resistant, dependable, versatile and economical spring-assisted, in-line check valve for a wide range of applications. Whether the fluid is liquid, gas or steam, the SCV® provides tight shut-off and protects other equipment in the system from water hammer. Its stainless steel construction insures a long service life.

Results 1 - 25 of 36

Prod. #	Size	Cold Working Pressure	Dimension A	Dimension B	Cv	Cracking Pressure CP	End Connection
8317	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	7	0.29 psig 0.020 bar	NPT
8368	DN 20 0.75 in	0 to 750 psig 0 to 51.7 barg	3.00 in 76 mm	2.13 in 54 mm	13	0.24 psig 0.017 bar	NPT
8369	DN 25 1 in	0 to 750 psig 0 to 51.7 barg	3.32 in 84 mm	2.54 in 65 mm	22	0.36 psig 0.025 bar	NPT
8371	DN 32 1.25 in	0 to 750 psig 0 to 51.7 barg	3.87 in 98 mm	3.06 in 78 mm	39	0.28 psig 0.019 bar	NPT
8373	DN 40 1.5 in	0 to 750 psig 0 to 51.7 barg	4.75 in 121 mm	3.44 in 87 mm	54	0.24 psig 0.017 bar	NPT
8374	DN 50 2 in	0 to 750 psig 0 to 51.7 barg	5.00 in 127 mm	4.4 in 112 mm	93	0.42 psig 0.029 bar	NPT
8311	DN 80 3 in	0 to 750 psig 0 to 51.7 barg	6.75 in 171 mm	6.19 in 157 mm	180	0.20 psig 0.014 bar	NPT
8317SW	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	7	0.29 psig 0.020 bar	Socket Weld
8368SW	DN 20 0.75 in	0 to 750 psig 0 to 51.7 barg	3.00 in 76 mm	2.13 in 54 mm	13	0.24 psig 0.017 bar	Socket Weld
8369SW	DN 25 1 in	0 to 750 psig 0 to 51.7 barg	3.32 in 84 mm	2.54 in 65 mm	22	0.36 psig 0.025 bar	Socket Weld
8371SW	DN 32 1.25 in	0 to 750 psig 0 to 51.7 barg	3.87 in 98 mm	3.06 in 78 mm	39	0.28 psig 0.019 bar	Socket Weld
8373SW	DN 40 1.5 in	0 to 750 psig 0 to 51.7 barg	4.75 in 121 mm	3.44 in 87 mm	54	0.24 psig 0.017 bar	Socket Weld
8374SW	DN 50 2 in	0 to 750 psig 0 to 51.7 barg	5.00 in 127 mm	4.4 in 112 mm	93	0.42 psig 0.029 bar	Socket Weld
8311SW	DN 80 3 in	0 to 750 psig 0 to 51.7 barg	6.75 in 171 mm	6.19 in 157 mm	180	0.20 psig 0.014 bar	Socket Weld
8317A20	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	7	0.29 psig 0.020 bar	NPT
8368A20	DN 20 0.75 in	0 to 750 psig 0 to 51.7 barg	3.00 in 76 mm	2.13 in 54 mm	13	0.24 psig 0.017 bar	NPT
8369A20	DN 25 1 in	0 to 750 psig 0 to 51.7 barg	3.32 in 84 mm	2.54 in 65 mm	22	0.36 psig 0.025 bar	NPT
8371A20	DN 32 1.25 in	0 to 750 psig 0 to 51.7 barg	3.87 in 98 mm	3.06 in 78 mm	39	0.28 psig 0.019 bar	NPT
8373A20	DN 40 1.5 in	0 to 750 psig 0 to 51.7 barg	4.75 in 121 mm	3.44 in 87 mm	54	0.24 psig 0.017 bar	NPT
8374A20	DN 50 2 in	0 to 750 psig 0 to 51.7 barg	5.00 in 127 mm	4.4 in 112 mm	93	0.42 psig 0.029 bar	NPT
8311A20	DN 80 3 in	0 to 750 psig 0 to 51.7 barg	6.75 in 171 mm	6.19 in 157 mm	180	0.20 psig 0.014 bar	NPT
8317HC	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	7	0.29 psig 0.020 bar	NPT
8368HC	DN 20 0.75 in	0 to 750 psig 0 to 51.7 barg	3.00 in 76 mm	2.13 in 54 mm	13	0.24 psig 0.017 bar	NPT
8369HC	DN 25 1 in	0 to 750 psig 0 to 51.7 barg	3.32 in 84 mm	2.54 in 65 mm	22	0.36 psig 0.025 bar	NPT
8371HC	DN 32 1.25 in	0 to 750 psig 0 to 51.7 barg	3.87 in 98 mm	3.06 in 78 mm	39	0.28 psig 0.019 bar	NPT

Results 1 - 25 of 36