


SCV-R® In-Line Restrictor Check Valves



The SCV-R® is an in-line spring-assisted check valve designed for applications requiring "higher cracking pressures" than the DFT Model SCV® check valve. The SCV-R® is a self-contained check valve that installs directly in a pipeline and contains all of the proven features of the SCV® check valve.

Results 1 - 25 of 103

Prod. #	Size	Cold Working Pressure	Dimension A	B (Dia.)	Cv	Cracking Pressure CP
8317-RC010	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	1 psig 0.069 bar
8317-RC015	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	1.5 psig 0.103 bar
8317-RC020	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	2 psig 0.138 bar
8317-RC025	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	2.5 psig 0.172 bar
8317-RC029	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	2.9 psig 0.200 bar
8317-RC036	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	3.6 psig 0.248 bar
8317-RC043	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	4.3 psig 0.296 bar
8317-RC050	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	5 psig 0.345 bar
8317-RC058	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	5.8 psig 0.400 bar
8317-RC065	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	6.5 psig 0.448 bar
8317-RC077	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	7.7 psig 0.531 bar
8317-RC092	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	9.2 psig 0.634 bar
8317-RC107	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	10.7 psig 0.738 bar
8317-RC123	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	12.3 psig 0.848 bar
8317-RC150	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	15 psig 1.034 bar
8317-RC181	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	18.1 psig 1.248 bar
8317-RC216	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	21.6 psig 1.489 bar
8317-RC250	DN 15 0.5 in	0 to 750 psig 0 to 51.7 barg	2.68 in 68 mm	1.62 in 41 mm	6	25 psig 1.724 bar
8368-RC035	DN 20 0.75 in	0 to 750 psig 0 to 51.7 barg	3.00 in 76 mm	2.13 in 54 mm	10	3.5 psig 0.241 bar
8368-RC040	DN 20 0.75 in	0 to 750 psig 0 to 51.7 barg	3.00 in 76 mm	2.13 in 54 mm	10	4 psig 0.276 bar
8368-RC044	DN 20 0.75 in	0 to 750 psig 0 to 51.7 barg	3.00 in 76 mm	2.13 in 54 mm	10	4.5 psig 0.310 bar
8368-RC050	DN 20 0.75 in	0 to 750 psig 0 to 51.7 barg	3.00 in 76 mm	2.13 in 54 mm	10	5 psig 0.345 bar
8368-RC056	DN 20 0.75 in	0 to 750 psig 0 to 51.7 barg	3.00 in 76 mm	2.13 in 54 mm	10	5.6 psig 0.386 bar
8368-RC061	DN 20 0.75 in	0 to 750 psig 0 to 51.7 barg	3.00 in 76 mm	2.13 in 54 mm	10	6.1 psig 0.421 bar
8368-RC066	DN 20 0.75 in	0 to 750 psig 0 to 51.7 barg	3.00 in 76 mm	2.13 in 54 mm	10	6.6 psig 0.455 bar

Results 1 - 25 of 103