


WLC® Wafer Check Valves



The DFT® Model WLC Wafer style Silent Check Valve is a lightweight, spring-assisted, in-line check valve that provides reliable, low maintenance service for a wide range of fluids and pressure/temperature combinations. The joint between the seat ring and body is sealed by the flange gasket upon installation preventing any leakage through the joint when the valve is in service.

Size/Class

- 1", 1 1/2" - 150/300
- 2" to 8" - 150/300
- 10" - 150

Results 1 - 25 of 61

Prod. #	Class	Size	Dimension A	Dimension B	Cv	Cracking Pressure CP	Body
9030-1	150/300	1 in	2.00 in 51 mm	2.88 in 73 mm	19	0.36 psig 0.025 bar	A216 Grade WCB
9033-1	150/300	1 in	2.00 in 51 mm	2.88 in 73 mm	19	0.36 psig 0.025 bar	A351 CF8M
9034-1	150/300	1.5 in	2.50 in 64 mm	3.75 in 95 mm	36	0.17 psig 0.012 bar	A216 Grade WCB
9035-1	150/300	1.5 in	2.5 in 64 mm	3.75 in 95 mm	36	0.17 psig 0.012 bar	A351 CF8M
9012	600	DN 25 1 in	2.38 in 60 mm	2.88 in 73 mm	19	0.36 psig 0.025 bar	A105
9013	600	DN 25 1 in	2.38 in 60 mm	2.88 in 73 mm	19	0.36 psig 0.025 bar	A479-316
9038	900/1500	DN 25 1 in	2.38 in 60 mm	3.13 in 80 mm	19	0.44 psig 0.030 bar	A105
9041	900/1500	DN 25 1 in	2.38 in 60 mm	3.13 in 80 mm	19	0.44 psig 0.030 bar	A479-316
9130	1500 (RTJ)	DN 25 1 in	2.38 in 60 mm	3.13 in 80 mm	19	0.44 psig 0.030 bar	A105
9131	1500 (RTJ)	DN 25 1 in	2.38 in 60 mm	3.13 in 80 mm	19	0.44 psig 0.030 bar	A479-316
9097	600	DN 40 1.5 in	2.88 in 73 mm	3.75 in 95 mm	23	0.44 psig 0.030 bar	A105
9019	600	DN 40 1.5 in	2.88 in 73 mm	3.75 in 95 mm	23	0.44 psig 0.030 bar	A479-316
9044	900/1500	DN 40 1.5 in	2.88 in 73 mm	3.88 in 99 mm	23	0.54 psig 0.037 bar	A105
9045	900/1500	DN 40 1.5 in	2.88 in 73 mm	3.88 in 99 mm	23	0.54 psig 0.037 bar	A479-316
9132	1500 (RTJ)	DN 40 1.5 in	2.88 in 73 mm	3.88 in 99 mm	23	0.54 psig 0.037 bar	A105
9133	1500 (RTJ)	DN 40 1.5 in	2.88 in 73 mm	3.88 in 99 mm	23	0.54 psig 0.037 bar	A479-316
9003	150/300	DN 50 2 in	2.63 in 67 mm	4.38 in 111 mm	57	0.24 psig 0.017 bar	A216 WCB
9004	150/300	DN 50 2 in	2.63 in 67 mm	4.38 in 111 mm	57	0.24 psig 0.017 bar	A351 CF8M
9006	600	DN 50 2 in	2.38 in 60 mm	4.25 in 108 mm	53	0.26 psig 0.018 bar	A216 Grade WCB
9007	600	DN 50 2 in	2.38 in 60 mm	4.25 in 108 mm	53	0.26 psig 0.018 bar	A351 CF8M
9009	900/1500	DN 50 2 in	2.75 in 70 mm	5.50 in 140 mm	48	0.24 psig 0.017 bar	A216 Grade WCB
9010	900/1500	DN 50 2 in	2.75 in 70 mm	5.50 in 140 mm	48	0.24 psig 0.017 bar	A351 CF8M
9086	1500 (RTJ)	DN 50 2 in	3.13 in 80 mm	5.50 in 140 mm	48	0.24 psig 0.017 bar	A216 Grade WCB
9091	1500 (RTJ)	DN 50 2 in	3.13 in 80 mm	5.50 in 140 mm	48	0.24 psig 0.017 bar	A351 CF8M
9014	150/300	DN 65 2.5 in	2.88 in 73 mm	5.13 in 130 mm	95	0.37 psig 0.026 bar	A216 Grade WCB

Results 1 - 25 of 61