




PH4201-005-P025



ORDERING INFO:

1. PH4201-2.5-P025 Pressure Sensor, 4-20mA Output, Titanium Housing, 0-2.5 PSIG, Poly Jacketed Cable, 25' Long
2. PH4201-005-P025 Pressure Sensor, 4-20mA Output, Titanium Housing, 0-5 PSIG, Poly Jacketed Cable, 25' Long
3. PH4201-010-P040 Pressure Sensor, 4-20mA Output, Titanium Housing, 0-10 PSIG, Poly Jacketed Cable, 40' Long
4. PH4201-015-P060 Pressure Sensor, 4-20mA Output, Titanium Housing, 0-15 PSIG, Poly Jacketed Cable, 60' Long

Applications

- Accurate measurement of wastewater and liquids containing debris, sludge or small particles
- Titanium is resistant to harsh environments, including brackish water, sludge or chemicals
- Superior performance compared to stainless steel
- Good for depths from 11.5 ft WC up to 34 ft WC

Custom Solutions

At times, OEMs, end users or military specifiers require a customized solution or sample product to test. Madison Company can design, manufacture and ship a custom switch or sensor in just six business days. Simply communicate the quantity and requirements to our technical sales staff. We will quote the product to establish budget and ROI. Following the quote approval, Madison engineers will design the switch or sensor that satisfies the application specifications, and provide proof of concept. Upon approval, we will build and ship the product or sample.

Related Products



PH4201-010-P040



PH4201-015-P060



PH4201-2.5-P025

View in-stock products ready to ship today at Madisonco.com/buy

PH4201 Series Technical Data Sheet

Hydrostatic Pressure Sensors

Hydrostatic Pressure Sensor Specifications

Model	Accuracy	Approvals	Input Voltage	Lead Wires	Max. Temp	Output	Pressure Range	Sensing Range	Type
PH4201-005-P025	±0.25% of Full Scale	CE, FM (available by special request)	10-35 VDC	25', Polyurethane Vented Cable	-10°F to 175°F (-23°C to 79°C). Non-freezing liquids	4-20mA Loop Current	0-5 PSI	0-11.5 ft WC	Pressure Level Sensor
PH4201-010-P040	±0.25% of Full Scale	CE, FM (available by special request)	10-35 VDC	40', Polyurethane Vented Cable	-10°F to 175°F (-23°C to 79°C). Non-freezing liquids	4-20mA Loop Current	0-10 PSI	0-23 ft WC	Pressure Level Sensor
PH4201-015-P060	±0.25% of Full Scale	CE, FM (available by special request)	10-35 VDC	60', Polyurethane Vented Cable	-10°F to 175°F (-23°C to 79°C). Non-freezing liquids	4-20mA Loop Current	0-15 PSI	0-34.5 ft WC	Pressure Level Sensor
PH4201-2.5-P025	±0.25% of Full Scale	CE, FM (available by special request)	10-35 VDC	25', Polyurethane Vented Cable	-10°F to 175°F (-23°C to 79°C). Non-freezing liquids	4-20mA Loop Current	0-2.5 PSI	0-5.75 ft WC	Pressure Level Sensor

View in-stock products ready to ship today at Madisonco.com/buy



Madison Company, Inc.
27 Business Park Drive
Branford, CT 06405

203-488-4477 or 800-466-5383
info@madisonco.com
www.madisonco.com

